



JARAMOGI OGINGA ODINGA UNIVERSITY OF SCIENCE AND TECHNOLOGY

UNIVERSITY EXAMINATIONS

2013/2014 ACADEMIC YEAR

**SECOND YEAR, FIRST SEMESTER FOR THE DEGREE OF BACHELOR OF
SCIENCE IN CONSTRUCTION MANAGEMENT**

TCM- 3211 SOIL MECHANICS

August 2013

TIME: 2 HOURS

INSTRUCTIONS TO CANDIDATES

This paper consists of 5 questions

Answer Question ONE and any other TWO Questions

QUESTION ONE

- a) State any TWO reasons why a better understanding of soil properties is necessary in constructing of building and civil engineering works.
(4 Marks)
- b) A soil mass has a bulk unit weight of 20kN/m^3 with water content of 19%. Taking specific gravity of the soil grains as 2.7, compute:
i. Dry unit weight
ii. Void ratio
iii. Porosity
iv. Degree of saturation
v. Submerged unit weight
(10 Marks)
- c) State SIX factors affecting permeability of soils
(6 Marks)
- d) Define the following Atterberg's limits
i. Liquid limit
ii. Plastic limit
iii. Shrinkage limit
(6Marks)
- e) State any TWO methods of soil site investigation
(4 Marks)

QUESTION TWO

- a) Distinguish between compaction and consolidation
(4 Marks)
- b) Distinguish between normally consolidated and over consolidated soils
(4 Marks)
- c) In a standard Proctor's Test, the mould of 1 liter capacity weighs 12.5N when empty. Successive trials gave results shown in Table 1. Determine the following:
i. Optimum moisture content
ii. Degree of saturation at maximum dry density.

Table 1

Weight of mould+weight of soil(N)	29.6	30.1	31.5	31.2	30.8
Water content (%)	16.7	18.6	21.0	21.7	23.5

(12 Marks)

QUESTION THREE

- a) State any FOUR applications for earth retaining structures in highway construction
(4 Marks)
- b) List any FOUR types of earth retaining structures
(4 Marks)
- c) A retaining wall with vertical back is 8m high. The density of the top 3m of fill is 17.15kN/m^3 and the angle of friction is 30° ; for the lower 5m, the values are

18.12kN/m³ and 35° respectively. There is a surcharge load on the horizontal surface of the fill equivalent to 11.8kN/m². Find the magnitude and point of application of the active thrust on the wall per lineal meter.

(12 Marks)

QUESTION FOUR

- In reference to shear strength of soils, state Mohr's- Coulomb theory.
(4 Marks)
- State any FOUR advantages of triaxial compression test over direct shear test.
(4 Marks)
- The results indicated in Table 2 were obtained from undrained shear box tests on specimens of sandy clay. The cross-section of the shear box was 60mmx60mm.

Table 2

Normal load (N)	200	400	800
Shear force at failure(N)	204	260	356

If a specimen of the same soil is tested in triaxial compression with a cell pressure of 100 kN/m², determine the total axial stress at which failure will be expected to occur.

(12 Marks)

QUESTION FIVE

- Distinguish between shallow and deep foundation.
(2 Marks)
- Distinguish between safe bearing capacity and allowable bearing capacity of soils
(4 Marks)
- Define soil stabilization and explain its purpose in construction process.
(4Marks)
- Explain why knowledge of position of groundwater table at a site is important before implementation of construction projects.
(4 Marks)
- Compute the ultimate bearing capacity of a strip footing of width 1.0m and 0.5m below the surface of a moist soil having cohesion of 0.2kg/cm² and angle of internal friction 36°. Assume the density of soil 2g/cc and the bearing capacity factors as N_c=48, N_q=35, N_γ =42. Also calculate safe bearing capacity if the factor of safety is 2.5.

(6 Marks)